

Trade name: edding Permanent Ink (red) contained in: edding 500, edding 550, edding 800, edding

Current version : 1.0.0, issued: 05.02.2023

Replaced version: -, issued: -

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

edding Permanent Ink (red) contained in: edding 500, edding 550, edding 800, edding 850, edding 3000, edding 3300

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Refill ink

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

Information provided by / telephone

+49 (0)4102 - 808-0

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 3; H226

STOT SE 3; H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07

Signal word

Warning

Hazardous component(s) to be indicated on label:

1-methoxy-2-propanol

Hazard statement(s)

Trade name: edding Permanent Ink (red) contained in: edding 500, edding 550, edding 800, edding

Current version : 1.0.0, issued: 05.02.2023

Replaced version: -, issued: -

Region: GB

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.
P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.
P405 Store locked up.
P501 Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

PBT assessment
The components of this product are not considered to be a PBT.
vPvB assessment
The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients
3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures
Chemical characterization

Mixture (preparation)

Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	1-methoxy-2-propanol		
	107-98-2 203-539-1 603-064-00-3 01-2119457435-35-0034	Flam. Liq. 3; H226 STOT SE 3; H336	< 75.00 wt%
2	ethanol		
	64-17-5 200-578-6 603-002-00-5 01-2119457610-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319	< 10.00 wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
2	-	Eye Irrit. 2; H319: C ≥ 50%	-	-

SECTION 4: First aid measures
4.1 Description of first aid measures
General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners.

After eye contact

Trade name: edding Permanent Ink (red) contained in: edding 500, edding 550, edding 800, edding

Current version : 1.0.0, issued: 05.02.2023

Replaced version: -, issued: -

Region: GB

Separate eyelids, wash the eyes thoroughly with water (15 min.).

After ingestion

Rinse out mouth and give plenty of water to drink. Call a doctor immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO)

5.3 Advice for firefighters

Use self-contained breathing apparatus. Cool endangered containers with water spray jet. Suppress gases/vapours/mists with water spray jet. Wear protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Trade name: edding Permanent Ink (red) contained in: edding 500, edding 550, edding 800, edding

Current version : 1.0.0, issued: 05.02.2023

Replaced version: -, issued: -

Region: GB

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

Incompatible products

Do not store together with: Acids; Alkalis; oxidizing agents

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
	2000/39/EC		
	1-Methoxypropanol-2		
	WEL short-term (15 min reference period)	568 mg/m ³	150 ppm
	WEL long-term (8-hr TWA reference period)	375 mg/m ³	100 ppm
	Skin resorption / sensibilisation	Skin	
	List of approved workplace exposure limits (WELs) / EH40		
	1-Methoxypropan-2-ol		
	WEL short-term (15 min reference period)	560 mg/m ³	150 ppm
	WEL long-term (8-hr TWA reference period)	375 mg/m ³	100 ppm
	Comments	Sk	
2	ethanol	64-17-5	200-578-6
	List of approved workplace exposure limits (WELs) / EH40		
	Ethanol		
	WEL long-term (8-hr TWA reference period)	1920 mg/m ³	1000 ppm

DNEL, DMEL and PNEC values

DNEL values (worker)

DNEL values (worker)				CAS / EC no	
No	Substance name				
	Route of exposure	Exposure time	Effect	Value	
1	1-methoxy-2-propanol			107-98-2 203-539-1	
	dermal	Long term (chronic)	systemic	183	mg/kg/day
	inhalative	Long term (chronic)	systemic	369	mg/m³
	inhalative	Short term (acut)	local	553.5	mg/m³
2	ethanol			64-17-5 200-578-6	
	dermal	Long term (chronic)	systemic	343	mg/kg/day
	inhalative	Long term (chronic)	svstemic	950	mg/m³

DNEL value (consumer)

DNEL value (consumer)					
No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	1-methoxy-2-propanol			107-98-2 203-539-1	
	oral	Long term (chronic)	systemic	33	mg/kg/day
	dermal	Long term (chronic)	systemic	78	mg/kg/day
	inhalative	Long term (chronic)	systemic	43.9	mg/m³

Trade name: edding Permanent Ink (red) contained in: edding 500, edding 550, edding 800, edding

Current version : 1.0.0, issued: 05.02.2023

Replaced version: -, issued: -

Region: GB

2	ethanol			64-17-5 200-578-6	
	oral	Long term (chronic)	systemic	87	mg/kg/day
	dermal	Long term (chronic)	systemic	206	mg/kg/day
	inhalative	Long term (chronic)	systemic	114	mg/m ³

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Type	Value	
1	1-methoxy-2-propanol		107-98-2 203-539-1	
	water	fresh water	10	mg/L
	water	marine water	1	mg/L
	water	Aqua intermittent	100	mg/L
	water	fresh water sediment	52.3	mg/kg
	with reference to: dry weight			
	water	marine water sediment	5.2	mg/kg
	with reference to: dry weight			
	soil	-	4.59	mg/kg
	with reference to: dry weight			
	sewage treatment plant	-	100	mg/L
2	ethanol		64-17-5 200-578-6	
	water	fresh water	0.96	mg/L
	water	Aqua intermittent	2.75	mg/L
	water	marine water	0.79	mg/L
	water	fresh water sediment	3.6	mg/kg dry weight
	water	marine water sediment	2.9	mg/L
	soil	-	0.63	mg/kg dry weight
	sewage treatment plant	-	580	mg/L
	secondary poisoning	-	0.38	mg/kg food

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment
Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified. Short term: filter apparatus, Filter A

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	butyl rubber		
Material thickness		0.5	mm
Breakthrough time	>	240	min

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

Trade name: edding Permanent Ink (red) contained in: edding 500, edding 550, edding 800, edding

Current version : 1.0.0, issued: 05.02.2023

Replaced version: -, issued: -

Region: GB

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation			
liquid			
Form			
liquid			
Colour			
red			
Odour			
characteristic			
pH value			
Value		7.5	
Source		Manufacturer	
Boiling point / boiling range			
Value		126 °C	
Source		Manufacturer	
Melting point/freezing point			
No data available			
Decomposition temperature			
Value		200 °C	
Source		Manufacturer	
Flash point			
Value		28 °C	
Source		Manufacturer	
Ignition temperature			
No data available			
Flammability			
No data available			
Lower explosion limit			
No data available			
Upper explosion limit			
No data available			
Vapour pressure			
Value		1100	hPa
Reference temperature		50	°C
Source		Manufacturer	
Relative vapour density			
No data available			
Relative density			
No data available			
Density			
Value		0.946	g/cm³
Reference temperature		20	°C
Source		Manufacturer	
Solubility			
No data available			
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.

Trade name: edding Permanent Ink (red) contained in: edding 500, edding 550, edding 800, edding

Current version : 1.0.0, issued: 05.02.2023

Replaced version: -, issued: -

Region: GB

1	ethanol	64-17-5	200-578-6
log Pow		-0.35	
Reference temperature		24	°C
with reference to	pH 7,4		
Method	OECD 107		
Source	ECHA		

Kinematic viscosity			
Value	12	sec	
Reference temperature	20	°C	
Type	dynamic		
Method	DIN cup 4 mm		
Source	Manufacturer		

Solvent separation test			
Value	3	%	

Particle characteristics			
No data available			

9.2 Other information

Other information			
No data available.			

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources. Protect from humid air and water.

10.5 Incompatible materials

Acids; Alkalies; Oxidizing agents

10.6 Hazardous decomposition products

Hydrogen

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		4016	mg/kg bodyweight
Species	rat		
Method	EC 440/2008, B.1		
Source	ECHA		
2	ethanol	64-17-5	200-578-6
LD50		10470	mg/kg bodyweight
Species	rat		
with reference to	95% ethanol in water		
Method	OECD 401		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Acute dermal toxicity			

Trade name: edding Permanent Ink (red) contained in: edding 500, edding 550, edding 800, edding

Current version : 1.0.0, issued: 05.02.2023

Replaced version: -, issued: -

Region: GB

No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50	>	2000	mg/kg bodyweight
Species	rat		
Method	440/2008/EC B.3.		
Source	ECHA		

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LC50		124.7	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Species	rabbit		
Method	EC 440/2008, B.4		
Source	ECHA		
Evaluation	non-irritant		
2	ethanol	64-17-5	200-578-6
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Species	rabbit		
Method	2004/73/EEC, B.5		
Source	ECHA		
Evaluation	non-irritant		
2	ethanol	64-17-5	200-578-6
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	irritant		
Evaluation/classification	Based on available data, the classification criteria are met.		

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Route of exposure	Skin		
Species	guinea pig		
Method	440/2008/EC B.6		
Source	ECHA		
Evaluation	non-sensitizing		
2	ethanol	64-17-5	200-578-6
Route of exposure	respiratory tract		
Source	ECHA		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Route of exposure	Skin		
Species	mouse		
Source	ECHA		
Evaluation	non-sensitizing		

Trade name: edding Permanent Ink (red) contained in: edding 500, edding 550, edding 800, edding

Current version : 1.0.0, issued: 05.02.2023

Replaced version: -, issued: -

Region: GB

Evaluation/classification	Based on available data, the classification criteria are not met.
---------------------------	---

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Type of examination		in vitro gene mutation study in bacteria	
Species		Salmonella typhimurium	
Method		OECD 471	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Type of examination		in vitro gene mutation study in mammalian cells	
Species		mouse lymphoma cells	
Method		OECD 476	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Type of examination		Genotoxicity in vivo	
Species		mouse	
Method		OECD 478	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Route of exposure		oral	
NOAEL			
Type of examination		2 generation study	
Species		mouse	
Method		OECD 416	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Route of exposure		inhalational	
NOAEL		>= 20000	ppm
Type of examination		Prenatal Developmental Toxicity Study	
Species		rat	
Method		OECD 414	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

STOT - single exposure	
No data available	

STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Route of exposure		oral	
Duration of exposure		14	week/s
Species		rat	
Target organ		kidneys	
Method		OECD 408	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Aspiration hazard	
No data available	

Delayed and immediate effects as well as chronic effects from short and long-term exposure	
--	--

Trade name: edding Permanent Ink (red) contained in: edding 500, edding 550, edding 800, edding

Current version : 1.0.0, issued: 05.02.2023

Replaced version: -, issued: -

Region: GB

Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness.
Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin.

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LC50		14200	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	EPA		
Source	ECHA		

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
EC50		5012	mg/l
Duration of exposure		48	h
Species	Ceriodaphnia dubia		
Method	ASTM Standard E 729-80		
Source	ECHA		

Toxicity to Daphnia (chronic)

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
NOEC		9.6	mg/l
Duration of exposure		9	day(s)
Species	Daphnia magna		
Source	ECHA		

Toxicity to algae (acute)

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
EC50		275	mg/l
Duration of exposure		72	h
Species	Chlorella vulgaris		
Method	OECD 201		
Source	ECHA		

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Type	aerobic biodegradation		
Value		96	%

Trade name: edding Permanent Ink (red) contained in: edding 500, edding 550, edding 800, edding

Current version : 1.0.0, issued: 05.02.2023

Replaced version: -, issued: -

Region: GB

Duration	28	day(s)
Method	OECD 301 E	
Source	ECHA	
Evaluation	readily biodegradable	
2	ethanol	64-17-5 200-578-6
Type	aerobic biodegradation	
Value	appr.	84 %
Duration	20	day(s)
Source	ECHA	
Evaluation	readily biodegradable	

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
log Pow		-0.35	
Reference temperature		24	°C
with reference to	pH 7,4		
Method	OECD 107		
Source	ECHA		

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	III
Hazard identification no.	30
UN number	UN1263
Proper shipping name	PAINT RELATED MATERIAL
Tunnel restriction code	D/E
Label	3

Trade name: edding Permanent Ink (red) contained in: edding 500, edding 550, edding 800, edding

Current version : 1.0.0, issued: 05.02.2023

Replaced version: -, issued: -

Region: GB

Environmentally hazardous
substance mark

Symbol "fish and tree"

14.2 Transport IMDG

Class	3
Packing group	III
UN number	UN1263
Proper shipping name	PAINT RELATED MATERIAL
EmS	F-E, S-E
Label	3
Marine pollutant mark	Symbol "fish and tree"

14.3 Transport ICAO-TI / IATA

Class	3
Packing group	III
UN number	UN1263
Proper shipping name	Paint related material
Label	3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3, 40
--	----------

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:	P5c
--	-----

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Trade name: edding Permanent Ink (red) contained in: edding 500, edding 550, edding 800, edding

Current version : 1.0.0, issued: 05.02.2023

Replaced version: -, issued: -

Region: GB

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.
Prod-ID 792508